BID SOLICITATION

Page 1 of 3 Printed: 1/25/2005



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS **CAPITOL HILL PROVIDENCE RI 02908**

BUYER:	LISA HILL
PHONE #:	(401) 222 - 2142 ext. 116

ENVIRONMENTAL MANAGEMENT DEM DIV OF PARKS AND RECREATION 2321 HARTFORD AVENUE L **JOHNSTON RI 02919** L

Т 0

I

Requisition Number(s): R74B053585

TERMS OF PAYMENT:

BID NUMBER: B04728

TITLE: BOX TRUCK

BID OPENING DATE AND TIME:

02/15/2005 11:00 AM

ENVIRONMENTAL MANAGEMENT Н **DEM DIV OF PARKS AND RECREATION** 2321 HARTFORD AVENUE ı Р **JOHNSTON RI 02919**

Т 0

Item	Class-Item	Quantity	Unit	Unit Price	Total
Item	THE FOLLOWING ADDITIONAL TERMS AND CONDITIONS APPLY TO THIS INVITATION FOR BIDS: 1. ALL VEHICLES MUST BE DELIVERED WITHOUT DEALER'S NAME OR ADVERTISING OF ANY TYPE VISIBLE ON THE BODY. 2. EACH VEHICLE DELIVERED TO THE STATE MUST BE ACCOMPANIED BY A "CERTIFICATE-OF ORIGIN" CONTAINING THE MANUFACTURER'S VEHICLE IDENTIFICATION NUMBER (VIN), THE NUMBER OF ENGINE CYLINDERS AND ENGINE TYPE, A GENERAL DESCRIPTION OF THE BODY, AND THE MODEL NAME OR NUMBER. CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO STATE OF RI/FLEET OPERATIONS, ONE CAPITOL HILL, PROVIDENCE, RI 02908 UNLESS THE VEHICLE IS BEING PURCHASED BY THE RHODE ISLAND STATE POLICE. IF SO, CERTIFICATE OR ORIGIN MUST BE ASSIGNED TO RHODE ISLAND STATE POLICE, 311 DANIELSON PIKE, NORTH SCITUATE, RI 02857. 3. BIDS MUST BE PREDICATED ON THE BASIS OF THE BIDDER'S FULL AND UNENCUMBERED TITLE TO THE VEHICLE(S) AS OF THE DATE OF DELIVERY TO THE STATE. BIDS SUBJECT TO LIEN OR ASSIGNMENT AT THE TIME OF DELIVERY TO THE STATE, OR WHICH STIPULATE THIRD PARTY OR JOINT PAYMENT, WILL BE REJECTED. 4. TITLE CERTIFICATES MUST BE PROVIDED AT THE TIME OF DELIVERY TO THE STATE. 5. WHERE THE FIRM SUBMITTING THE BID IS ACTING AS AN AGENT FOR ANOTHER CORPORATE ENTITY, (SPECIFICALLY WITH RESPECT TO LEASE ARRANGEMENTS), THE BID MUST IDENTIFY THE CORPORATION WHO WILL BE NAMED IN ANY SUBSEQUENT AWARD AS THE BIDDER OF RECORD. 6. UNLESS OTHERWISE INDICATED, ALL VEHICLES WILL BE DELIVERED TO STATE FLEET OPERATIONS AT	Quantity	Unit	Unit Price	Total

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DO NOT SIGN BID ON THIS PAGE!
RIVIP VENDOR ID#:

USE CERTIFICATION COVER FORM.

BID SOLICITATION

Page 2 of 3 Printed: 1/25/2005

ı

L

L Т

0

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS **CAPITOL HILL PROVIDENCE RI 02908**

BID NUMBER:	B04728
TITLE: BOX TRUCK	

BID OPENING DATE AND TIME:

02/15/2005 11:00 AM

S	ENVIRONMENTAL MANAGEMENT
Н	DEM DIV OF PARKS AND RECREATION
ı	2321 HARTFORD AVENUE
Р	JOHNSTON RI 02919

Т 0

ENVIRONMENTAL MANAGEMENT DEM DIV OF PARKS AND RECREATION 2321 HARTFORD AVENUE **JOHNSTON RI 02919**

BUYER: LISA HILL

PHONE #: (401) 222 - 2142 ext. 116

Requisition Number(s): D74D0E2E0E

JST			
1.00	EA		
OF :S			
	JST 1.00	OF	1.00 EA

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DELIVERY:	RIVIP VENDOR ID#:			
TERMS OF PAYMENT:	DO NOT SIGN BID ON THIS PAGE!			

USE CERTIFICATION COVER FORM.

BID SOLICITATION

Page 3 of 3 Printed: 1/25/2005



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS **CAPITOL HILL PROVIDENCE RI 02908**

	DID NOMBER. BOTTE
	TITLE: BOX TRUCK
BUYER: LISA HILL PHONE #: (401) 222 - 2142 ext. 116	BID OPENING DATE AND TIME: 02/15/2005 11:00 AM
VIDONIMENTAL MANAGEMENT	S ENDURANTAL MANAGEMENT

ENVIRONMENTAL MANAGEMENT DEM DIV OF PARKS AND RECREATION 2321 HARTFORD AVENUE L **JOHNSTON RI 02919** L Т 0

Requisition Number(s): R74B053585

TERMS OF PAYMENT:

S H	ENVIRONMENTAL MANAGEMENT DEM DIV OF PARKS AND RECREATION
ı	2321 HARTFORD AVENUE
Р	JOHNSTON RI 02919
т	
_	

RID NUMBER: B04728

Item	Class-Item	Quantity	Unit	Unit Price	Total
	CONTACT: STEVEN T. WRIGHT AT 401-222-2632 FOR ANY ADDITIONAL INFORMATION.			TOTAL:	

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

TERMO OF RAVAIENT	DO NOT SIGN BID ON THIS PAGE!
DELIVERY:	RIVIP VENDOR ID#:

USE CERTIFICATION COVER FORM.

Specifications 16' Box Truck

UD2600G Manufacturer's latest model year

GVWR: not to exceed 25,995 LBS and not to be under 25,495 LBS

171.3" wheel base / ca 139.1"

B.B.C. 82.52" OAL. 300.4"

Gross Payload 16,550 Lbs

Turning radius ft. 24.3

Engine: MD230-24 valve turbo/intercooled diesel

In-line 6 cylinder, direct-injection

230 HP @ 2500 RPM

506 Lb. Ft. Torque @ 1500 RPM

Displacement 469 in. [7.684 L]

Dry replaceable cylinder liner

Air compressor 14.1 CFM @ 2600 RPM [nominal]

Fuel system electronically controlled common rail system

Air Cleaner 11 in., paper filter type [Donaldson]

Cold starting aid automatic electric glow plug

Viscous type drive fan

Exhaust Brake:

Electrically controlled, pneumatically activated butterfly valve in exhaust pipe

Chassis Frame:

Ladder type, channel section side rail Dim. In inches 9.84 x 3.15 x 0.31 Assembled width 33.9 in Section Modulus 26.6 Yield strength 42,600 RMB [in-lb]: 1,133,000

Fuel tank mounted to left side, capacity 50 gallons

Cab: Color: PPG color paint code: 46204 Dark Jade Metallic

Cab: Forward control, steel construction tilting cab

Cab suspension w/shocks absorbers

Air conditioner: Standard Glass tinted laminated

Door locks driver and passenger electric controlled

Door vent driver ventilating type

Windows, driver and passenger, electric control

Driver seat: height and seat back angle adjustable, with air

suspension. Colt coverer, high back type

Keyless entry system

Steering wheel tilt and telescopic

Passenger seat with fold down center consol seat

Windshield wipers dual electric-driven, intermittent and 2 speed

Front axle capacity # 9,480

Axle type "I" beam

Suspension semi-elliptic leaf springs

Shock absorbers telescopic type

Rear Axle:

Rated axle capacity 18,080 lbs

Axle type full floating banjo housing

Suspension semi-elliptic leaf springs with auxiliary springs

Wheels and tires:

Tires front single, highway tread

Rear: dual traction type 11 R 22.5-14PR [tubeless radial]

Wheels: steel disc. Type, 8 hole, 7.50 x 22.5 in., offset 6.38 in

Transmission:

Allison automatic LCT 2400P 5 forward speeds & 1 reverse

Brake System

Service brakes anti-lock braking system

Dual line, air over-hydraulic brake system

Front: internal expanding, two leading shoe, self-adjusting drum

brakes

Drum Diameter x lining width x lining thickness: $15.75 \times 4.72 \times 0.59$

in.

Rear: Internal expanding, dual two leading shoes self adjusting drum

brakes

Drum diameter x lining x width x lining: $15.75 \times 6.10 \times 0.59$ in.

Parking Brake: Rear wheel parking brake air operated

Air Tanks:

Supply: 641 in. 3

Front service: 549 in. 3 Rear service: 641 in. 3 Total: 1, 831 in. 3 Air dryer: standard

Vehicle to have a minimum of a 2 two year roadside assistance program, on call 24 hours per day seven [7] days a week

Minimum 2 two year unlimited mile warranty with an extended power train including the transmission for 60 months or 100,000 mile from date in service.

Morgan Dry Freight "Fast Track" 16 Van Body Specifications

Model # GVSD09116FT

Body dimensional information:

Inside height: 91.12" Inside length: 190.88" Inside width: 91.9"

Rear Door opening: 88.00" w x 85.25" h

Chassis Information:

Make: Nissan

Model # UD2600 E/G/K/L/N/S WB:171.3

Sub-frame: 3" I-beam cross-members on 12" centers with 4" long rail

mylar tape on bottom rails, 2 extra cross-members

2 Full mount U bolts

Morgan 24" x 36" black mud-flaps 1 1/8" laminated hardwood flooring

Plastic covered whiting pre-painted white rear door

Rear Frame: Galvannealed for overhead door with recessed tail lites

Compatible pre-drilled plugged holes in the rear frame posts

Endplate reinforcement

Galvannealed header post gusset

Threshold-rear: steel diamond flush to rear 1/8" x 23" routed edge

into floor

Side Post: steel Z on 16" centers no door curbside

Skins side: .040 aluminum pre-painted white Rivets: rivets for front and sidewalls-16 Body

Liner side: 3/8" plywood full

Scuff: galvanized steel 12 ga 16" high

Interior ties e-track: Series e-track recessed rows [1] locate 48" from

top of floor to center of track, front series e track recessed.

Interior ties tie rings: tie ring "D" recessed row [1] locate rings at 40" centerline to floor on each side of body. Post station+ 10.62, 24, 40, 56, 72, 88, 104, 120, include two [2] tie rings evenly spaced on front wall aligned with side row 1

Front End: aerodynamic aluminum radii with steel Z posts

Skins-Front: .040, aluminum pre-painted white

Liner-Front: Morgan reinforced full height plywood- 20" high steel

Roof: .032, aluminum

Top Radius: Aerodynamic aluminum radius and corner caps

Interior Light: Dome with switch at rear, extra dome dome on same

circuit

Lift-gate: interlift ilp-33 80 in. x 48" in. wedge 3300 lb capacity

Lift-gate bumper: lift-gate narrow structural Lift-gate cutoff switch with lite installation

Grab handle: aluminum 12" grab handle- bolted curbside and roadside

Exterior lights: Per FMVSS-108 with sealed harness system standard

tailites in rear corner post foreign chassis Crash plate in front end with ¾" plywood

20 in. high steel scuff with leg returned under floor to 1st crossmember

Paint: Rear frame steel white IMRON Accessories: series E 85-94

45/64"

Reflective tape: conspicuity tape installation

END

